

# SPECIFICATIONS

|   |  |
|---|--|
| Model   | AL-MEISTER ALM3230   |
| Paper Feeding Method                          | Pick Up By Rubber Roller On Upper Side Of Paper                              |
| Feeder Pressure Adjustment                    | Square Holes + Lever   |
| Lamination Method                             | Heat Roller Method   |
| Film Width                                    | 320mm  |
| Film Material                                 | PET  |
| Film Thickness                                | 30mic - 125mic   |
| Film Type                                     | Gloss & Matt   |
| Paper Thickness                               | 0.07 ~ 0.25mm  |
| Paper Size(Width)                             | 257 ~ 330mm  |
| Paper Size(Length)                            | 182 ~ 457mm  |
| Laminating Speed                              | 1.0m/min fixed   |
| Heating Method                                | Internal Heating Method  |
| Temperature Range                             | OFF, 80 ~ 130°C  |
| Warm-Up Time                                  | Approx. 15 min.  |
| Cutting                                       | With Margin(3.0mm), Without Margin   |
| Cut Adjust                                    | Front: -30~+ 5mm, Rear: -5~+ 30mm  |
| Fine Adjustment Function Of Slitting Position | Available(Free Fixing Type: Long Hole + Screw)<br>Minimum Finish Size: 248mm |
| Stand   | Not Available  |
| Fine Mode                                     | Not Available  |
| Long Mode                                     | Available (optional)   |
| Power Consumption                             | 1200W  |
| Dimensions                                    | W 1272 × D 630 × H 470mm<br>(Assembled, including roll-up lever              |
| Weight  | Aprx. 50kg   |
| RFID  | Equipped (One on lower side)   |

\*Corners are square cut.  
\*Cutter and Trimmer Blades have a approximate life cycle of 50.0000 cuts, A4 size paper  
\*Warm-up time may differ according to the environment.

AL-MEISTER®  
**ALM3230**  
Auto Laminator



Everbest 74  
5741 PM Beek en Donk  
Tel. +31(0) 492 392 303  
www.fujipla.eu

*The next generation of Fujipla Automatic Digital Laminators.  
Fully automated operation will reduce both production time and costs.  
ALM3230 can laminate simply at the touch of a button.  
Easy switching from Encapsulation (with margin) to four edge trimmed  
(no margin). Suitable for A4, A3 (trimmed) and SRA3 and banner length  
lamination (un-trimmed)*

## Automatic Feeder

The advanced automatic feeder will handle up to 200 sheets of paper, based on 80gsm. An anti-skew mechanism is built into the feeder tray allowing correction of sheets before feeding. The positive wide feeding rollers ensure stable sheet feeding for excellent lamination. Quality feeding, less operator involvement, higher efficiency.

## Features:

- \* Fully automatic machine feeds, laminates, cuts and trims, delivers fully finished.
- \* Hot roller system, scratch free lamination and low noise output.
- \* Speed 1.0 m/min fixed.
- \* Cut adjust for front and back, cutting has adjustment from +0.5mm to -30mm.
- \* Skew correction and stable feed combine to eliminate skewed feeding.
- \* IC tag reader equipped.

### AL-MEISTER® **ALM3230** Auto Laminator



## Automatic Trimming

AL-Meister automatically detects the length of the paper and selects the appropriate settings, A4 & A3 size.

There are two types of configuration:

- \* Trimming with margin, which guarantees the laminated paper is durable and waterproof.
  - \* Trimming without margin, which provides image enhancement and surface protection.
- The modes can be changed easily and the margins are fully adjustable.

## Professional Hot Roller System

Hot roller system incorporating high performance heaters. Perfect temperature control for smooth and flawless lamination. Scratch free lamination for perfect results.

A variety of film is available for every job.  
Thickness 38-75-125 mic. (gloss & mat)