

EXCELTOPIC-380

DESKTOP POD LAMINATOR

- Ideal for:
 - BOPP Lamination
 - Digital BOPP Lamination
 - PET Lamination
 - Nylon Lamination
 - Sleeking™ Foils:
- Usage of eco-friendly GMP Thermalami® film
- Perfect solution for all digital prints.



FEATURES


- Ideal entry level machine for Sleeking (gloss / matt / holographic / metallic).
- Semi-automatic paper feed with patented gap controlsystem.
- No air compressor to reduce noise output.
- Strengthened laminating pressure for bond and Sleekingsystem.
- Integrated tension control and de-curling device.
- Optional patented embossing rollers.
- Automatic burst cutting system.
- Integrated perforation solution.
- Hot roller designed to avoid silvering.
- Lamination of up to 1.5m guillotine ready sheets/per minute.
- Up to SRA3 (380mm x 500mm)



Using household power supply (220 ~ 240V)

APPLICATIONS

- Posters
- Pop-up signs
- Menus
- Book covers
- Photographs
- Photo albums
- Business cards
- Gift certificates
- Labels (with Micronex Label films)
- Greetings cards



BURSTING ROLLER



TOP AND IN-LINE PERFORATOR



TEMPERATURE SENSOR INSIDE ROLLER



REMOVABLE FEEDING TABLE

EXCELTOPIC-380

BASIC PATTERNS OF EMBOSSING ROLLER (OPTIONAL)



FINE
TEXTURE



LEATHER
TEXTURE



SPARKLE
TEXTURE



SILKY
TEXTURE



LINEN
TEXTURE

Model Name	EXCELTOPIC -380
Dimensions (WxLxH)	700 x 630 x 560mm
Laminating Speed	1.5m/min ~ 8m/min
Paper Size (WxL)	Max: 380 x 500mm (optional 1200mm) Min: 180 x 210mm
Laminating Films	<ul style="list-style-type: none"> • Single Side <ul style="list-style-type: none"> - Polynex (20 ~ 43mic) - Perfex (25mic) - Nylonx (27 ~ 44mic) • Micronex (8 ~ 10mic) <ul style="list-style-type: none"> - Gloss/Matt/Holographic
Sleeking™	Gloss / Matt / Holographic / Metallic
Substrate Thickness	120 ~ 350g/m ²
Front Roller Diameter (Top)	high gloss chrome Ø 80
Front Roller Diameter (Bottom)	silicon Ø 80
Rear Roller Diameter	silicon Ø 40
Power Requirements	AC 220 ~ 240V, 50/60Hz, 12A
Power Consumption	2.8kw
Warm-up Time	5 minutes
Heating System	Infrared Heater
Laminating Temperature	Max. 150°C
Temperature Control	Jog dial
Speed Control	Jog dial
Display System	LCD Panel
Roller Pressure	Manual
Film Core Size	77mm (3")
Temperature Sensing Method	Thermo-couple inserted in the roller shell

GNP reserves the right to change specifications without prior notice.