

EXCELAM-Q SERIES

LARGE FORMAT ROLL LAMINATOR

- Perfect machines to produce a wide range of services in a copy shop, graphic printing shop or photo shop environment.

FEATURES

- Easy to use for external re-winder tension control.
- Applied dual core adaptor for film roll and stronger unwinder shaft.
- Enhanced clutch function and easy to use for outer pressure tension knob.
- Hot and cold lamination. (Both rollers fully heated)
- Speed and temperature control.
- Automatic power shut-off and stand-by system.
- Top and bottom independent temperature control.
- Back trimmer for easy web separation.



| Model Name | EXCELAM-Q1100 RS | EXCELAM-Q1670 RS |
|-----------------------|--|--|
| Dimensions (WxLxH) | 1500 x 710 x 1250mm | 2000 x 710 x 1250mm |
| Max. Laminating Speed | 3m/min | 3m/min |
| Max. Laminating Width | 1100mm | 1670mm |
| Laminating Films | 25mic ~ 500mic | 25mic ~ 500mic |
| Substrate Thickness | 80g/m ² ~ 350g/m ² | 80g/m ² ~ 350g/m ² |
| Thickness Mount | 13mm | 13mm |
| Front Roller Diameter | 80mm | 80mm |
| Rear Roller Diameter | 60mm | 60mm |
| Power Requirements | 220 ~ 240V, 50/60Hz | 220 ~ 240V, 50/60Hz |
| Power Consumption | 3300W, 15A | 3300W, 15A |
| Warm-up Time | 22 minutes | 25 minutes |
| Heating System | Hot Roller Internal Infrared Heater | Hot Roller Internal Infrared Heater |
| Operating Temperature | Max. 150°C | Max. 150°C |
| Speed Control | Key Pad | Key Pad |
| Temperature Control | Key Pad | Key Pad |
| Pressure Control | Manual (7 steps) | Manual (7 steps) |
| Film Core | 77mm / Dual | 77mm / Dual |
| Cooling System | Blower | Blower |
| Main Motor | DC Geared Motor | DC Geared Motor |
| Re-winder Motor | Link to Main Motor | Link to Main Motor |
| Net Weight | 193kg | 249kg |