

# EXCELAM-Q1600 COMBI / RSER

## EXCELAM-Q1600 INDEX

- R:** Rewind
- S:** Stand
- ER:** Extra Rewind

## FEATURES

- High speed laminating of up to 5m/minute.
- Strengthened main motor for better drive torque and durability.
- Rewinder connected to the powerful main motor.
- Top rewinder for releasing liner.
- Easy to use for outer rewinder tension control.
- Designed for dual film core and strong unwinder shaft.
- Mounting up to 13mm.



Model Name	Excelam-Q1600 Combi / RSER
Dimensions (WxLxH)	1840x 750 x 1200mm
Max. Laminating Speed	5m/min
Max. Laminating Width	1600mm
Laminating Films	25mic - 500mic
Substrate Thickness	80g/m <sup>2</sup> - 350g/m <sup>2</sup>
Max. Thickness Mount	13mm
Power Requirements	220 - 240V, 50/60Hz
Power Consumption	2000W, 8.3A
Warm-up Time	5 minutes
Heating System	Infrared Heater
Laminating Temperature	Max. 150°C
Temperature Control	Key Pad
Speed Control	Key Pad
Film Core	77mm / Dual
Type of Main Motor	DC-Geared Motor
Type of Rewinder Motor	Link to Main Motor