




LAMI CORPORATION INC.



Azalea 1600CL

Product Introduction

1. Product




Safety sensor
High sensitivity sensor prevents finger pinch



Easy operation handle
- Roller clearance




Easy speed adjustment
- Dial system speed adjustment
- 0m~6.0m/min



Emergency stop



Heat assist (40°C)



Re-winding system
Optional shaft holder



Easy film set new shaft
- Light shaft with scale

2. Features



Model	Azalea 1600CL
Max. Laminating Width	1,670 mm
Max. Substrate Thickness	10 mm
Max. Speed	6.0 m/min
Roller Heating	40°C
Warm up time	8 min (approx)
Upper Roller Type	Crowned
Below Roller type	Crowned
Roller Clearance	Manual 0-10mm
Roller Diameter	88 mm
Electrical Requirements	100V 50/60hz
Power consumption	1,100 Watt
Size (width X depth X height)	1,940 X 520 X 1,100 mm
Weight	150 kg
Feeding tray length	190 mm


3. Features of Azalea1600CL

No.	Sales points	Detail
1	Manual roller UP & DOWN function	Non-step adjustment with simple operation handle
2	High speed	Max. 6.0m/min
3	Easy speed adjustment	0m~6.0m/min adjustment by dial system
4	Heat assist function	40°C (Warm up time just 8 min)
5	High sensitivity safety sensor	Stops when fingers are too close to roller
6	Foot switch	Run/stop, roller up/down
7	Crown roller	Both roller crowned → Stable finish
8	Detailed adjustment	Adjusting roller pressure in detail
9	Pressure memorize function	The last pressure used is memorized even power off
10	Feeding tray length 19cm	For stable lamination process
11	Special shaft	Light shaft with the scale → Easy film setting
12	Compact size (rewinding system inside)	Suitable for any work space
13	Roller Diameter 88mm	Roller length 1670mm
14	Rewinding system and optional shaft	2 shaft holders at the front side

4. Sales Points

Non-step roller Up & Down

- Adjustment in detail (-2mm ~+8mm)
- Easy operation with simple dial
- Improve productivity with easy usage




Easy operation with simple operation panel

- Check the status: Run/stop, reverse, heat assist ready
- Adjust the speed: easy adjustment by dial

High pressure & heat assist roller

- High pressure by 88mm diameter roller
- Heat assist (40°C) allows beautiful finish
- Two crowned roller makes the pressure even



4. Sales Points

High sensitivity sensor

- Sensor detects the finger pinch and stop until safe
- Prevents finger pinch
- When machine is running / roller is lowering



Easy film set with special shaft

- Light shaft which makes film set easy
- Fix the film position with the printed scale

Rewinding system and optional shaft holder

- Stable rewinding system
- 2 shaft holders at the front side

