## **IDEAL 2245**

# max. 13 sheets

Innovative, compact deskside shredder with EASY-Touch for intuitive operation

← 22 cm →

Level P-2		4 n	nm	st	rip	cut	

Sheet capacity\*: 11-13 | 9-11

Level P-4 3 x 25 mm particle cut

Sheet capacity\*: 6-7 | 5-6

**Level P-5** 2 x 15 mm particle cut


Sheet capacity\*: 4-5 | 3-4



#### Technical specifications

Volume	20 litres (shred bin)		
Power	230 V / 50 Hz**		
Motor capacity	150 Watt single phase motor		

\*\* other voltages available



 Dimensions
 428 x 345 x 213 mm (H x W x D)

 Weight
 6.5 kg / 7.5 kg (particle cut)

**ID-No.** 11224501

GS certificate-No. DP 10031

#### **Product characteristics**

Easy-to use deskside shredder for environmentally conscious users. EASY-Touch multifunction switch element for stand-by / stop (off) / reverse with integrated optical signals for the operational status of the shredder. Photo cell controlled automatic start and stop. Automatic reverse and power cut-off. ZERO ENERGY standby mode: complete, automatic disconnection from power supply after 30 minutes. Transparent safety flap in the feed opening as additional safety element. Quiet, powerful and energy-efficient single phase motor. Double motor protection. High-quality, paper clip proof cutting shafts from special hardened steel with lifetime guarantee. Attractive shred bin from impact-resistant plastic. Practical handle for lifting off the shredder unit from the bin. Magnetic switch for automatic stop if the shredder unit is removed from the shred bin (2245 CC).



<sup>\*</sup> A4 paper 70 g/m² | 80 g/m²

## **IDEAL 2245**

#### **Features**



#### **SOLID STEEL CUTTING SHAFTS**

Robust and durable: high-quality paper clip proof cutting shafts with lifetime guarantee under conditions of fair wear and tear.




#### PRACTICAL HANDLE

A practical handle is integrated into the design for lifting off the shredder unit from the shred bin when full.



#### **SAFETY FLAP**

The safety flap in the feed opening is an additional safety element to keep fingers, ties or other objects away from the cutting shafts.



#### **EASY-TOUCH MULTIFUNCTION SWITCH**

Easy operation is guaranteed with the EASY-Touch multifunction switch for stand-by / stop (off) / reverse and optical signals for the operational status of the shredder.

















certificate no. **DP 10031** dated 31.01.2014



### **GS Test Certificate**

Name and address of the

holder of the certificate:

(customer):

Krug & Priester GmbH & Co. KG Simon-Schweitzer-Straße 34

72336 Balingen

Name and address of the

Manufacturer:

see above

Product designation: Paper Shredder

Type: 11221002, 11223002, 11227001, 11224501

Testing based on: DIN EN 60950-1:2011-01+A12:2011-08

EN 60950-1:2006-04+A11:2009-03+A1:2010-03+A12:2011-02

IEC 60950-1:2005-12+AMD1:2009-12 Information technology equipment -

Safety; Part 1: General requirements

EN 12100-2:2004 Safety of machinery – Basic concepts, general principles for design; Part 2: Technical principles EN ISO 13857:2008 Safety of machinery – Safety distances to prevent hazard zones being reached by upper and lower

limbs

Remarks: This Test Certificate replaces the Test Certificate DP 10031

dated 25.09.2012.

The type tested meets the requirements specified in article 21 para. 1 of the German Product Safety Act. The holder of the certificate is entitled to affix the GS mark shown overleaf to the products complying with the type tested. At that, the holder of the certificate shall observe the conditions specified overleaf.

The present certificate including the right to affix the GS mark is valid until: 21.03.2015

Further provisions concerning the validity, the extension of the validity and other conditions are laid down in the Rules of Procedure for Testing and Certification of August 2012.



Signature (Dipl.-Ing. Vogl)

Postal address: Postfach • D-65173 Wiesbaden • Office: Rheinstr. 6-8 • D-65185 Wiesbaden Phone: +49 (0) 611/131-8219 • E-Mail: pruefstelle-dp@bgetem.de 612.17-So/Ho • Test report: A 09194 • Produktschlüsselnummer: 001.1001

