IDEAL **2604**

Centralised data protection — suitable for continuous operation

SPS - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY_SWITCH - intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bin is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode. Photo cell controlled automatic start and stop. ECC - Electronic Capacity Control - indication of the used sheet capacity during shredding process. Convenient 260 mm feed opening. High quality paper clip proof¹ cutting shafts from special hardened steel. Models IDEAL 2604 and IDEAL 2604 CC suitable for shredding the most common CDs/DVDs. 30 years guarantee¹ on the cutting shafts. Quiet but powerful 640 Watt single phase motor for continuous operation. Sturdy Twin Drive System with fully closed gear box housing. High-quality wooden cabinet, mobile on castors. Convenient shred bin. Approx. 100 litres volume for the shreds. Dimensions (H x W x D): 926 x 495 x 470 mm, Weight: approx. 48 kg.

SHREDDER TYPES

4 mm strip cut

Sheet capacity*: 30-32 / 26-28
Security level 2

4 x 40 mm cross cut

Sheet capacity*: 25-27 / 21-23 Security level 3

2 x 15 mm cross cut

Sheet capacity*: 15-17 / 13-15 Security level 4

0.8 x 12 mm micro cut

Sheet capacity*: 10-12 / 8-10
Security level 5

0.8 x 5 mm super micro cut

Sheet capacity*: 5-7 / 4-6
Security level »Level 6«



¹ not applicable for models 2604 MC with 0.8 x 12 mm micro cut and 2604 SMC with 0.8 x 5 mm super micro cut.

^{*} A4 paper, 70 g/m² / 80 g/m²

Features



SOLID STEEL CUTTING SHAFTS IDEAL office shredders are available for all security levels of the DIN 32 757 standard. First class quality with special hardened, solid steel cutting shafts. 30 years guarantee on the cutting shafts (except fine cut models).



EASY_SWITCH Innovative multifunction control element with integrated optical signals for the operational status.



SAFETY PROTECTION SYSTEM Electronically controlled safety flap in the feed opening to keep fingers, ties or other objects away from the cutting shafts.



ECC - ELECTRONIC CAPACITY CONTROL ECC - Electronic Capacity Control indicates the used sheet capacity during shredding process to avoid paper jams.